

Product data sheet

Satellite insert 3-wire, power supply



Reference number

1723 NE

Satellite insert 3-wire, power supply

for covers JUNG HOME ref.-no.: BT .. 17101 .., BT .. 17102 .., BT .. 17181 .., BT .. 17182 .., BT 17361 ..
for covers eNet ref.-no.: FM .. 1700 .., FM .. 1701 ..
for covers LB Management ref.-no.: .. 1700 .., .. 1702 .., .. 1750 D .., .. 17180 .., .. 17280 ..
for covers KNX RF ref.-no.: .. 1091 1ST RF .., .. 1092 1ST RF ..

Intended use

- Satellite operation of suitable inserts
- Satellite for extending the detection field of motion and presence detectors
- Central control of multiple main devices
- Operation with suitable cover
- Installation in flush box with dimensions according to DIN 49073
- Neutral conductor required

Technical data

Rated voltage:	AC 230 V ~
Mains frequency:	50/60 Hz
Ambient temperature:	-20 ... +45 °C
Connection	screw terminals
single wire:	1 x 0.5 ... 4.0 mm ² 2 x 0.5 ... 2.5 mm ²
stranded without ferrule:	1 x 0.5 ... 4.0 mm ² 2 x 0.5 ... 2.5 mm ²
stranded with ferrule:	1 x 0.5 ... 4.0 mm ² 2 x 0.5 ... 1.5 mm ²
Total length of satellite cable:	max. 100 m