

# Product data sheet

## DALI rotary controller TW



## Reference number

1740 DSTE

## DAI rotary controller TW

### DAI-2 single-master

## Intended use

- Brightness setting for luminaires with DALI interface
- Setting of colour temperature for luminaires with DALI Device Type 8 for tunable white acc. to IEC 62386-209
- Installation in flush box with dimensions according to DIN 49073

### Product characteristics

- The DALI rotary controller TW takes power from the DALI voltage, which must be supplied by an external DALI power supply in accordance with IEC 62386-101.
- Saving of colour temperature limiting values
- Saving of basic brightness and switch-on brightness
- Certified acc. to IEC 62386-101 and -103 (Single Master)
- The device functions as a DALI-2 single-master and should not be combined with other DALI controllers.

Centre plates:

AS / A ranges: ref.-no. A 1740 ..

CD range: ref.-no. CD 1740 ..

LS range: ref.-no. LS 1740 ..., .. 1740 ..

## Technical data

(external DALI power supply acc. to IEC 62386-101 required)

Rated voltage DALI: DC 16 V (typ.)

Power consumption: max. 2 W

Ambient temperature:  $-5 \dots +45\text{ }^{\circ}\text{C}$

Colour temperature setting: 2,000 ... 10,000 K

