

Product data sheet

Centre plate for modular jack sockets



Reference number

569-25 NWE

Centre plate (screw fixing) with inscription field 6 x 37 mm

(with supporting frame, screw fixing only)

shutter with spring

inner dimensions of keystone mount 14,8 x 20,7 mm

for modular jack sockets

TE Connectivity (Tyco Electronics / AMP NETCONNECT)

for cable Ø max. 10 mm:

EMT-jack, Cat. 5e, 180° ref.-no. 0-0188650-5

EMT-jack, Cat. 5e, 90° ref.-no. 0-0188650-6

for cable Ø max. 6.5 mm:

EMT-jack, Cat. 5e, 180° ref.-no. 0-0338038-1

EMT-jack, Cat. 5e, 90° ref.-no. 0-0338038-2

Toolless Jack, Cat. 3 unshielded: ref.-no. 0-1116603-x

Toolless Jack, Cat. 5e unshielded: ref.-no. 0-1116604-x,

Toolless Jack, Cat. 5e shielded: ref.-no. 0-1339015-1

Toolless Jack, Cat. 6 unshielded: ref.-no. 0-1116605-x,

Toolless Jack, Cat. 6 shielded: ref.-no. 0-1339016-1

MTRJ-LWL jack: ref.-no. 1278414-1

for 2 sockets

Spare part:

Transparent cover with paper inlay ref.-no.: CD 20 NA

Inscription fields may be customised using our GRAPHIC TOOL (jung.group/gt).

Thermoplastic (breakproof) high-gloss

Colour:

ivory

Material:

thermoplastic