

Product data sheet

1-gang push-button 10 A / 250 V ~ (without lens)



Reference number

634 A

1-gang push-button 10 A / 250 V ~ (without lens)

Can be converted into pull cord push-button by means of pull cord insert ref.-no. 34. with screwless terminals for rigid wires up to 2.5 mm²

Illumination possible with lamp ref.-no. 90/95 (230 V), 96-.. (low voltage), or LED lamp ref.-no. 90-LED.. (230 V) or 961248 LED.. (low voltage).

Lens and pull cord insert not included. Please order separately.

Lens / symbols: ref.-no. 33 ..

Ground plate

non-flammable, ref.-no.: 328

Notice!

Installation only by persons with relevant electrical knowledge and experience!*)

Use only with original JUNG product components approved for this article.

By inappropriate installation you endanger

- your own life,
- the life of the user of the electrical appliance.

By inappropriate installation you risk a high loss by damage, e.g. risk by fire.

You assume personal liability in cause of injury to persons or damage of appliances.

Please contact a skilled electrician!

*) Required technical knowledge for installation:

For installation, especially the following technical knowledge is required:

- the 5 important safety rules: disconnect from mains, secure against reconnecting, verify parts are free of voltage, ground and short-circuit, cover or block off adjacent live parts
- select adequate tools, measuring devices and personal protective equipment
- evaluate measuring results
- selection of the electrical installation material to secure switch-off conditions
- IP protection levels
- installation of the electrical installation material
- type of electric power grid (TN system, IT system, TT system) and the resultant connection terms (common grounding, protective ground, required additional action etc.)

Colour:

ivory

Version:

1-pole, 1-way NO contact with separate contacts for indicator light

Material:

duroplastic