


Product data sheet

KNX push-button standard 2-gang



Reference number

A 1072 1ST

KNX push-button standard 2-gang

for rockers ref.-no. .. 102 .., .. 102 KO5 .. of the AS and A ranges
project design and commissioning with ETS5 or a more recent version
ETS product family: Push-button
Product type: 2-gang push-button

Intended use

- Operation of loads, e.g. light on/off, dimming, blinds up/down, brightness values, temperatures, calling up and saving light scenes, etc.
- Installation in flush box with dimensions according to DIN 49073

Product characteristics

- KNX medium: TP 256
- Operating concept (rocker or button) adjustable for each operating area
- Button evaluation (single-area operation or dual-area operation) adjustable
- One or two functions per operating area
- Integrated bus coupling unit
- One status LED per operating area – red
- KNX Data Secure compatible with ETS 5.7.3 or higher
- Can be updated with the ETS Service App

Accessories:

external sensor ref.-no.: FF NTC

Technical data

KNX

KNX medium:	TP 256
Security:	X-mode
Commissioning mode:	S-mode
Rated voltage:	DC 21 ... 32 V SELV
Current consumption KNX:	5.9 ... 8.2 mA
Connection, KNX:	connection terminal
Connection cable:	EIB-Y (St)Y 2x2x0.8
Protection class:	III
Ambient conditions	
Ambient temperature:	-5 ... +45 °C
Storage/transport temperature:	-25 ... +70 °C

