


# Product data sheet

## Standard automatic switch 2.2 m



### Reference number

A 3281 WW

### KNX automatic switch 2.2 m

#### Standard

for bus coupling unit 3 ref.-no.: 2073 U

Degree of protection IP44 is ensured with sealing kit ref.-no. AS A 50 DS and "IP44 frame" of the respective design range.

**IP44 suitable only for interiors**

ETS product family: Physical sensors

Product type: Movement

#### Intended use

- Requirement-oriented control of lighting and other electrical loads
- Mounting on bus coupling unit 3 (ref.-no.: 2073 U)

#### Product characteristics

- Automatic switching of lighting depending on the thermal movement and ambient brightness
- 2 PIR sensors
- Detection range 180°
- Integrated brightness sensor
- Switch-off brightness can be set
- Output functions: Switching, staircase lighting function, switching with forced position, value transmitter, light scene extension, operating mode setting for room temperature controller
- Extension of the detection area by way of operating several devices as main unit or extension unit
- Sensitivity can be set manually
- Status LEDs
- Manual switching on the device

### Technical data

|                  |               |
|------------------|---------------|
| Colour           | white         |
| Range            | AS/A range    |
| Material         | thermoplastic |
| Version          | Standard      |
| Mounting height: | 1.10 / 2.20 m |

### Thermoplastic (breakproof) high-gloss

#### Colour:

white

#### Material:

thermoplastic

**IP** Degree of protection IP44 is ensured with sealing kit ref.-no. AS A 50 DS and "IP44 frame" of the respective design range.