

# Product data sheet

SCHUKO® socket with safety lock



## Reference number

AL 1520 NAKLSL AN

**SCHUKO® socket 16 A / 250 V ~**

with hinged lid (with spring)  
with inscription field 9 x 39 mm  
with safety lock (24 different locks)  
with 2 keys  
with enhanced contact protection / shutter (Safety Plus)  
with screwless terminals for rigid and untreated flexible wires up to 2.5 mm²

without claws: ref.-no. with additional "N", e.g.: ..1520 N..  
Supporting frame, claws and claw screws are integrated into the earth protection.

### Spare part:

Transparent cover with paper inlay ref.-no.: LS 90 NA

Spare key ref.-no.: 802 SL to 825 SL (When ordering, please indicate lock number, e. g. 813 SL)

Inscription fields may be customised using our GRAPHIC TOOL ([jung.group/gt](http://jung.group/gt)).

### Notice!

**Installation only by persons with relevant electrical knowledge and experience!\*)**

**Use only with original JUNG product components approved for this article.**

By inappropriate installation you endanger

- your own life,
- the life of the user of the electrical appliance.

By inappropriate installation you risk a high loss by damage, e.g. risk by fire.

You assume personal liability in cause of injury to persons or damage of appliances.

**Please contact a skilled electrician!**

**\*) Required technical knowledge for installation:**

For installation, especially the following technical knowledge is required:

- the 5 important safety rules: disconnect from mains, secure against reconnecting, verify parts are free of voltage, ground and short-circuit, cover or block off adjacent live parts
- select adequate tools, measuring devices and personal protective equipment
- evaluate measuring results
- selection of the electrical installation material to secure switch-off conditions
- IP protection levels
- installation of the electrical installation material
- type of electric power grid (TN system, IT system, TT system) and the resultant connection terms (common grounding, protective ground, required additional action etc.)

### metal colours (thermoplastic lacquered)

#### Colour:

anthracite

#### Material:

thermoplastic lacquered

**IP** Degree of protection IP44 is ensured with sealing gasket ref.-no. 551 WU and "IP44 frame" of the respective design range.

**P** Individual colour printing possible