Product data sheet

2-gang SCHUKO® socket with contact protection

Reference number
AL 5020 KI AN-L

2-gang SCHUKO® socket 16 A / 250 V ~

with enhanced contact protection / shutter (Safety Plus)
to be installed into one flush box with 60 mm Ø
with screwless terminals for rigid wires up to 2.5 mm²

Notice!
Installation only by persons with relevant electrical knowledge and experience!*)
Use only with original JUNG product components approved for this article.
By inappropriate installation you endanger

- your own life,
- the life of the user of the electrical appliance.

By inappropriate installation you risk a high loss by damage, e.g. risk by fire.
You assume personal liability in cause of injury to persons or damage of appliances.
Please contact a skilled electrician!
***) Required technical knowledge for installation:**
For installation, especially the following technical knowledge is required:

- the 5 important safety rules: disconnect from mains, secure against reconnecting, verify parts are free of voltage, ground and short-circuit, cover or block off adjacent live parts
- select adequate tools, measuring devices and personal protective equipment
- evaluate measuring results
- selection of the electrical installation material to secure switch-off conditions
- IP protection levels
- installation of the electrical installation material
- type of electric power grid (TN system, IT system, TT system) and the resultant connection terms (common grounding, protective ground, required additional action etc.)

metal colours (duroplastic lacquered)

Colour:
anthracite

Material:
duroplastic lacquered

ALBRECHT JUNG GMBH & CO. KG
Volmestraße 1
58579 Schalksmühle

Telefon +49 (0) 23 55/80 60
Telefax +49 (0) 23 55/80 6189
E-Mail kundencenter@jung.de