

# Product data sheet

SCHUKO® socket for cable ducts, 2-gang



## Reference number

AS 1522 NA

**SCHUKO® socket for cable ducts 16 A / 250 V ~**

**2-gang**

**wired**

**with 1 inscription field 12 x 55.5 mm**

**with screwless terminals for rigid and untreated flexible wires up to 2.5 mm<sup>2</sup>**

Cover with integrated frame for installation into cable duct boxes

Supporting frame is integrated into the earth protection.

dimensions: 80.5 x 151.5 mm

## Spare part:

Transparent cover with paper inlay ref.-no.: AS 81 NA

## Notice!

**Installation only by persons with relevant electrical knowledge and experience!\*)**

**Use only with original JUNG product components approved for this article.**

By inappropriate installation you endanger

- your own life,
- the life of the user of the electrical appliance.

By inappropriate installation you risk a high loss by damage, e.g. risk by fire.

You assume personal liability in cause of injury to persons or damage of appliances.

**Please contact a skilled electrician!**

## \*) Required technical knowledge for installation:

For installation, especially the following technical knowledge is required:

- the 5 important safety rules: disconnect from mains, secure against reconnecting, verify parts are free of voltage, ground and short-circuit, cover or block off adjacent live parts
- select adequate tools, measuring devices and personal protective equipment
- evaluate measuring results
- selection of the electrical installation material to secure switch-off conditions
- IP protection levels
- installation of the electrical installation material
- type of electric power grid (TN system, IT system, TT system) and the resultant connection terms (common grounding, protective ground, required additional action etc.)

**Duroplastic (scratch-proof) glossy**

**Colour:**

ivory

**Material:**

duroplastic