

# Product data sheet

SCHUKO® socket with inscription field SCHUKO® socket with contact protection and inscription field



## Reference number

ES 1521 KINA

**SCHUKO® socket 16 A / 250 V ~**

**with enhanced contact protection / shutter (Safety Plus)**

**with inscription field 12 x 55 mm**

**with screwless terminals for rigid and untreated flexible wires up to 2.5 mm<sup>2</sup>**

**with inscription field 9 x 58 mm**

Supporting frame is integrated into the earth protection.

with screw terminals for rigid and flexible wires up to 2.5 mm<sup>2</sup>

without claws: ref.-no. with additional "N", e.g.: ..1521 N..

Supporting frame, claws and claw screws are integrated into the earth protection.

### Spare part:

Transparent cover ref.-no.: M 20 NA

### Spare part:

Transparent cover with paper inlay ref.-no.: CD 90 NA

Inscription fields may be customised using our GRAPHIC TOOL ([jung.group/gt](http://jung.group/gt)).

### Notice!

**Installation only by persons with relevant electrical knowledge and experience!\*)**

**Use only with original JUNG product components approved for this article.**

By inappropriate installation you endanger

- your own life,
- the life of the user of the electrical appliance.

By inappropriate installation you risk a high loss by damage, e.g. risk by fire.

You assume personal liability in cause of injury to persons or damage of appliances.

**Please contact a skilled electrician!**

**\*) Required technical knowledge for installation:**

For installation, especially the following technical knowledge is required:

- the 5 important safety rules: disconnect from mains, secure against reconnecting, verify parts are free of voltage, ground and short-circuit, cover or block off adjacent live parts
- select adequate tools, measuring devices and personal protective equipment
- evaluate measuring results
- selection of the electrical installation material to secure switch-off conditions
- IP protection levels
- installation of the electrical installation material
- type of electric power grid (TN system, IT system, TT system) and the resultant connection terms (common grounding, protective ground, required additional action etc.)

### Metal versions

#### Colour:

stainless steel

#### Material:

stainless steel 1.4303 X4 CrNi 18-12

-  Individual colour printing possible
-  Individual laser engraving possible