


# Product data sheet

## SCHUKO® socket with USB charger



### Reference number

LC 1520-15 CA 220

### SCHUKO® socket with USB charger

with enhanced contact protection / shutter (Safety Plus)  
with 1 USB port type A and 1 USB port type C  
with screwless terminals for rigid and untreated flexible wires up to 2.5 mm<sup>2</sup>

Installation in flush box with dimensions according to DIN 49073  
depth of flush box (inner dimension): min. 57 mm

### Accessories:

Frame 28 mm structure height ref.-no.: LS 98.. HBF ..

### Technical data

|                                |                             |
|--------------------------------|-----------------------------|
| Rated voltage:                 | AC 220 ... 250 V ~          |
| Mains frequency:               | 50/60 Hz                    |
| Rated current:                 | 16 A                        |
| Output voltage USB:            | DC 5 V                      |
| Output current USB (total):    | 3 A                         |
| Stand-by power:                | ≤ 25 mW                     |
| Ambient temperature:           | +5 ... +35 °C               |
| Storage/transport temperature: | -20 ... +70 °C              |
| Connection mode:               | screwless terminals         |
| single wire:                   | 1.5 ... 2.5 mm <sup>2</sup> |
| stranded without ferrule:      | 1.5 ... 2.5 mm <sup>2</sup> |

### matt lacquered

### Colour:

vert 31

### Material:

duroplastic lacquered



Individual colour printing possible