

# Product data sheet

## SCHUKO® socket with USB charger



### Reference number

LC 1520-18C 260

### SCHUKO® socket with USB charger

with enhanced contact protection / shutter (Safety Plus)  
 with 1 USB port type C  
 with quick charge function (JUNG Quick Charge®)  
 with screwless terminals for rigid and untreated flexible wires up to 2.5 mm<sup>2</sup>

Installation in flush box with dimensions according to DIN 49073  
 depth of flush box (inner dimension): min. 57 mm

### Accessories:

Frame 28 mm structure height ref.-no.: LS 98.. HBF ..

### Technical data

|                                |                             |
|--------------------------------|-----------------------------|
| Rated voltage:                 | AC null ... null V ~        |
| Mains frequency:               | 50/60 Hz                    |
| Rated current:                 | 16 A                        |
| Output voltage USB:            | DC 9 V / DC 5 V             |
| Output current USB:            | 2 A / 3 A                   |
| Stand-by power:                | ≤ 25 mW                     |
| Ambient temperature:           | +5 ... +35 °C               |
| Storage/transport temperature: | -20 ... +70 °C              |
| Connection mode:               | screwless terminals         |
| single wire:                   | 1.5 ... 2.5 mm <sup>2</sup> |
| stranded without ferrule:      | 1.5 ... 2.5 mm <sup>2</sup> |



**matt lacquered**

**Colour:**  
orange vif

**Material:**  
duroplastic lacquered



Individual colour printing possible