

Product data sheet

Centre plate for modular jack sockets



Reference number

LS 1969-25 WE

Centre plate (snap-on fixing)

(with supporting frame, screw fixing only)

shutter with spring

inner dimensions of keystone mount 14,8 x 20,7 mm

for modular jack sockets

TE Connectivity (Tyco Electronics / AMP NETCONNECT)

for cable Ø max. 10 mm:

EMT-jack, Cat. 5e, 180° ref.-no. 0-0188650-5

EMT-jack, Cat. 5e, 90° ref.-no. 0-0188650-6

for cable Ø max. 6.5 mm:

EMT-jack, Cat. 5e, 180° ref.-no. 0-0338038-1

EMT-jack, Cat. 5e, 90° ref.-no. 0-0338038-2

Toolless Jack, Cat. 3 unshielded: ref.-no. 0-1116603-x

Toolless Jack, Cat. 5e unshielded: ref.-no. 0-1116604-x,

Toolless Jack, Cat. 5e shielded: ref.-no. 0-1339015-1

Toolless Jack, Cat. 6 unshielded: ref.-no. 0-1116605-x,

Toolless Jack, Cat. 6 shielded: ref.-no. 0-1339016-1

MTRJ-LWL jack: ref.-no. 1278414-1

for 2 sockets

Thermoplastic (breakproof) high-gloss

Colour:

ivory

Material:

thermoplastic

P Individual colour printing possible

L Individual laser engraving possible