

# Product data sheet

## Standard automatic switch 2.2 m



### Reference number

LS 3281 SWM

### KNX automatic switch 2.2 m

#### Standard

for bus coupling unit 3 ref.-no.: 2073 U

Degree of protection IP44 is ensured with sealing kit ref.-no. AS CD 50 DS and "IP44 frame" of the respective design range.

#### IP44 suitable only for interiors

ETS product family: Physical sensors

Product type: Movement

### Intended use

- Requirement-oriented control of lighting and other electrical loads
- Mounting on bus coupling unit 3 (ref.-no.: 2073 U)

### Product characteristics

- Automatic switching of lighting depending on the thermal movement and ambient brightness
- 2 PIR sensors
- Detection range 180°
- Integrated brightness sensor
- Switch-off brightness can be set
- Output functions: Switching, staircase lighting function, switching with forced position, value transmitter, light scene extension, operating mode setting for room temperature controller
- Extension of the detection area by way of operating several devices as main unit or extension unit
- Sensitivity can be set manually
- Status LEDs
- Manual switching on the device

### Technical data

|                  |                         |
|------------------|-------------------------|
| Colour           | matt graphite black     |
| Range            | LS range                |
| Material         | thermoplastic lacquered |
| Version          | Standard                |
| Mounting height: | 1.10 / 2.20 m           |

### matt lacquered

#### Colour:

matt graphite black

#### Material:

thermoplastic lacquered



Degree of protection IP44 is ensured with sealing kit ref.-no. AS CD 50 DS and "IP44 frame" of the respective design range.