

# Product data sheet

## Key card holder RFID



### Reference number

LS CARD RFID WW

### Key card holder RFID

for energy saving unit ref.-no.: ESU 230-2

The key card holder RFID is used to keep the hotel card and to ensure a high level of safety and energy savings, since all possibly powered electrical loads are switched off with an adjustable delay after removing the hotel card. The key card holder RFID will be completed with the energy saving unit.

Customised adjustment of the lens colour/brightness and switch-off delay of the second relay are possible before ordering. Subsequent changes are possible with configuration card (ref.-no. CONFIG CARD) which can be ordered separately.

For customisation of the key card holder, please visit the following website: [jung.group/hotelcard](http://jung.group/hotelcard)

The intended use and the product characteristics refer to the complete device, consisting of energy saving unit and key card holder RFID.

### Product characteristics

- Operation with RFID cards according to RFID standard ISO/IEC 14443 and ISO/IEC 15693
- 2 1-way NO contacts, one of them with configurable switch-off delay
- Status indication with RGB lens
- Lens is dimming down 30 s after inserting the card
- Switch-off delay is signalled by RGB lens after removing the card

### Thermoplastic (breakproof) high-gloss

**Colour:**  
white

**Material:**  
thermoplastic

-  Individual colour printing possible
-  Individual laser engraving possible