

Product data sheet

Service terminal



Reference number

NRS DZT 20 WW

Service terminal

- Central remote signalling from up to 20 alarms
- Optical and acoustical signalling
- Two-line display for indication of the alarms
- Programmable alarm messages with up to 16 characters for allocating the alarms
- 20 electrically isolated inputs with one ground
- Evaluation of stand-by current or operating current
- Suppression of the acoustical alarms for 20 seconds
- Green presence push-button
- Yellow alarm suppression push-button
- Programmable with the PC
- USB-cable and Software (multi-language) included
- Power supply 24 V DC
- Inputs 24 V DC
- For screw-fixing in a wall box without claws
- Dimensions: 100 x 148 x 26 mm (W x H x D)

Technical data

Supply voltage:	DC 24 V $\pm$ 12.5 %
Current consumption:	max. 30 mA
Ambient temperature:	+5 ... +40 °C
Connection mode:	screwless terminals
single wire:	Ø 0.3 ... 1.4 mm
Cable type:	J-Y(St)Y
Distance emergency signal – service terminal:	max. 500 m
Inputs	
Voltage range:	DC 24 V $\pm$ 12.5 %
Current consumption:	typical 2 mA

Thermoplastic (breakproof) high-gloss

Colour:
white

Material:
thermoplastic