

Product data sheet

Emergency system set with UPS



Reference number

NRS LS 0834-2 WWM

Emergency system set with UPS

consists of pull cord push-button, emergency signal, reset button, power supply and UPS module

screw fixing only, without claws

with 1-gang frames

Installation note on UPS module: intall into deep flush box

The JUNG emergency system is a well-conceived, complete set for emergency calls in WCs or en-suite bathrooms in old people's homes and nursing homes or WC facilities in public buildings. It ensures that a person in need of help can sound the alarm in an emergency and meets all the safety-related requirements in accordance with DIN VDE 0834.

The emergency system is a modular distributed system.

The following five components are available as a complete emergency system set:

- Pull cord push-button

An emergency call can be triggered in the bathroom/WC via an easily accessible pull cord. The pull cord push-button can also be installed in the middle of the room on the ceiling so that it is easily accessible for people in need of help. A red lamp on the switch signals that the emergency call has been triggered successfully.

- Emergency signal

The emergency signal can e.g. be installed outside next to the WC door or landing door. A triggered emergency call is signalled visually by a red LED and acoustically by a buzzer. Both signals can, if required, be changed from continuous light/continuous tone to flashing light/pulsing tone.

- Reset button

The reset button is installed next to the door in the same room as the pull cord push-button. The assisting personnel can reset the triggered call.

- Power supply for the emergency call system with DC 24 V

- UPS module for bridging power failures

The **service unit**, **service terminal** and the **call button** are separately available. The service unit can be installed in addition to the components of the emergency set e.g. in a staff room or lobby. A green button indicates presence while a yellow button suppresses the acoustic emergency signal for 20 seconds. The call button has an additional control for triggering an emergency call.

The emergency system is available for the AS / A, CD and LS design ranges to complete a unique design in a building. The design frames are part of the system set.

For a system extension all components are available separately.