

Технический паспорт продукта

JUNG HOME датчик движения 1,1 м



Ссылочный номер

BT LC 17181 233

JUNG HOME датчик движения 1,1 м

для вставки «освещение» арт.: 1701 SE, 1701 PSE, 1704 ESE, 1702 SE, 1710 DE, 1711 DE, 1712 DE, 1713 DSTE, 1723 NE

Использование по назначению

- Automatic switching of lighting depending on the thermal movement and ambient brightness
- Wireless linking with JUNG HOME system devices
- Operation with system insert for switching or dimming or satellite insert 3-wire
- Wall installation on system insert

Характеристики

- Commissioning and operation using JUNG HOME app with mobile device (smartphone or tablet) via Bluetooth®
- Switch for continuous ON/OFF or automatic operation
- Detection range extended by combining several JUNG HOME motion detectors or via satellite input
- Заслонка для ограничения зоны обнаружения
- Multi-coloured status indicator
- Disabling of local operation
- Free linking of the motion sensor with actuator in the insert or wirelessly with other JUNG HOME devices
- Up to 16 time programs control the functions of the respective insert (ON/OFF switching or dimming)
- Staircase lighting function (automatic switch-off) with switch-off warning
- Период последействия, задержка включения, задержка выключения
- Disabling function and forced guidance: Continuous ON/OFF or ON/OFF for fixed time
- Activate/deactivate automatic functions using the JUNG HOME app
- Автоматическое обновление даты и времени при соединении со смартфоном
- Time programs with sunrise or sunset (astro timer)
- Maximum and minimum brightness adjustable, with dimming insert
- Switch-on with last brightness or fixed switch-on brightness, with dimming insert
- Warm dimming (changing of the colour temperature with simultaneous brightness increase), with DALI insert
- Including the load in areas (groups), central functions and scenes
- Evaluation of the satellite inputs (if present) for controlling the system insert
- Bluetooth® Mesh for fully encrypted wireless communication and repeater function
- Can be updated using JUNG HOME app

Available in future via update:

(Notes on updates and schedules can be found at jung.group/junghome)

- Night light function with period for brightness reduction, with dimming insert
- Hotel function (orientation light instead of OFF), with dimming insert
- Calling a scene with movement

Технические характеристики

Температура окружающей среды: -5 ... +45 °C

Температура транспортировки:	-25 ... +70 °C
Температура хранения:	-5 ... +45 °C
Относительная влажность:	20 ... 70 % (без конденсата)
Степень защиты:	IP20
Точность хода в месяц:	± 13 s
Резерв питания:	мин. 4 ч
Угол обнаружениягол:	180°
Высота монтажа:	1,10 м
Чувствительность:	0, 25, 50, 75, 100 %
Установка освещённости:	около 5 ... 1.000 лк (и дневной режим)
Период последействия:	около 1 с ... 240 мин.
Радиочастота:	2402,0 ... 2480,0 МГц
Мощность передачи:	макс. 10 мВт (класс 1.5)
Дальность передачи в зданиях:	около 30 м
матовое исполнение, лакиров	
Цвет:	l'ocre rouge mouen
металл:	
термопласт лакиров.	