

Технический паспорт продукта

JUNG HOME кнопка, 1 группа с символами «стрелки»



Ссылочный номер

BT LS 17101 P

JUNG HOME кнопка, 1 группа с символами «стрелки»

для вставки «жалюзи» арт.: 1730 JE и 1731 JE

для вставки «освещение» арт.: 1701 SE, 1701 PSE, 1704 ESE, 1702 SE, 1710 DE, 1711 DE, 1712 DE, 1713 DSTE, 1723 NE

Использование по назначению

- Manual and automatic operation of e.g. blinds, shutters, awnings, lighting or fans
- Wireless linking with JUNG HOME system devices
- Operation with system insert for switching, dimming, blind or satellite insert 3-wire

Характеристики

- Commissioning and operation using JUNG HOME app with mobile device (smartphone or tablet) via Bluetooth®
- Top, bottom and full-surface operation with up to 2 linked functions per rocker
- Use the buttons to control areas (groups) or to call up scenes
- Use the buttons to operate wirelessly linked JUNG HOME devices
- Use the buttons to trigger the disabling function and forced guidance
- Multi-coloured status indicator with optional night mode
- Feedback of the load status using status LED
- Disabling of local operation
- Including the load in areas (groups), central functions and scenes
- До 16 временных программ управляют функциями соответствующей системной вставки (включение, выключение, диммер, перемещение жалюзи, регулировка температуры)
- Staircase lighting function (automatic switch-off) with switch-off warning
- Период последействия, задержка включения, задержка выключения
- Activate/deactivate automatic functions using the JUNG HOME app
- Автоматическое обновление даты и времени при соединении со смартфоном
- Time programs with sunrise or sunset (astro timer)
- Maximum and minimum brightness adjustable, with dimming insert
- Switch-on with last brightness or fixed switch-on brightness, with dimming insert
- Warm dimming (changing of the colour temperature with simultaneous brightness increase), with DALI insert
- Ventilation position, running time, slat change-over time, change-over time for direction change and inverse operation adjustable, with blind insert
- Disabling function and forced guidance: Lock-out protection, continuous ON/OFF or ON/OFF for a fixed time
- Evaluation of the satellite inputs (if present) for controlling the system insert
- Wind alarm via connection of weather sensors to satellite input, with blinds insert
- Bluetooth® Mesh for fully encrypted wireless communication and repeater function
- Can be updated using JUNG HOME app

Available in future via update:

(Notes on updates and schedules can be found at jung.group/junghome)

- Night light function with period for brightness reduction, with dimming insert
- Hotel function (orientation light instead of OFF), with dimming insert

Технические характеристики

Температура окружающей среды:	+5 ... +45 °C
Температура транспортировки:	-25 ... +70 °C
Точность хода в месяц:	± 13 s
Резерв питания:	около 4 ч
Радиочастота:	2402,0 ... 2480,0 МГц
Мощность передачи:	макс. 10 мВт (класс 1.5)
Дальность передачи в зданиях:	около 30 м

Дюропласт (устойчивый к механическим повреждениям) глянцевый

Цвет:
слоновая кость

металл:
дуропласт