

Технический паспорт продукта

JUNG HOME шлюз



Ссылочный номер

BT S GATEWAY

JUNG HOME шлюз

including power supply
including LAN cable

Использование по назначению

- Connecting JUNG HOME devices to myJUNG services, e.g. for voice control
- Connecting JUNG HOME devices to other smart home systems via the local network
- Only suitable for use in indoor areas that are free of dripping and splashing water
- For wall installation or as desktop device (top-hat rail mounting with separately available adapter for rail mounting, ref.-no.: MA-REG)

Характеристики

- Commissioning and operation using JUNG HOME app with mobile device (smartphone or tablet) via Bluetooth®
- Bluetooth® Mesh for fully encrypted wireless communication and repeater function
- Encrypted communication via myJUNG services e.g. with services from Alexa, Google Home
- 3 status LEDs for commissioning and operation support
- Button for commissioning and for factory reset
- RJ45 socket and included LAN cable for connecting to WLAN router
- Can be updated using JUNG HOME app
- Encrypted communication with local network e.g. with Smart Visu Server (requirement: JUNG HOME gateway from version 1.3.1 and SV-SERVER2 from version 1.2.1850), wibutler pro 2 and Mediola gateway

The gateway has been awarded the "Smart Home - Information Security Tested" certificate by the VDE Institute.

Accessories:

mounting adapter for DIN rail ref.-no.: MA-REG

Технические характеристики

Gateway

Потребляемая мощность в режиме ожидания:	< 2 Вт
Размеры (Д x Ш x В):	102 x 102 x 28 мм
Рабочая температура:	-5 ... +45 °C
Температура транспортировки:	-20 ... +70 °C
Степень защиты:	IP20
Радиочастота:	2402,0 ... 2480,0 МГц
Дальность передачи в зданиях:	около 30 м
Мощность передачи:	10 дБм / 10 мВт, класс 1.5
LAN:	1 x 10/100/1000 Мбит/с

Power supply

Напряжение питания:	ПЕРЕМ. ТОК 230 В
Частота сети:	50/60 Гц
Выходное напряжение:	5 V SELV

Подключение USB:

Micro USB-B

Исполнение:
с Europlug